





MODELLI DISPONIBILI MODELS AVAILABLE MODELOS DISPONIBLES				 NEW! 2019
	Cod. 01.000.215	Cod. 01.000.239	Cod. 01.000.224	Cod. 01.000.257
Capacità Capacity Capacidad	3,50 gr/h	3,50 gr/h	3,50 ÷ 7 gr/h Con potenza regolabile with adjustable power con potencia ajustable	5/10/15/20 gr/h Con potenza regolabile with adjustable power con potencia ajustable
Timer Temporizador	2 ore/hours/horas	2 ore/hours/horas	2 ore/hours/horas 12 ore a richiesta/hours on request horas bajo solicitud	135 min con timer digitale with digital timer con temporizador digital
Rumorosità Noisiness Ruido	<40dB	<40dB	<40dB	<40dB
Alloggiamento Housing Alojamiento	Cabinet in acciaio verniciato Cabinet made of painted steel Alojamiento de acero pintado	Cabinet in acciaio inossidabile Stainless steel cabinet Alojamiento en acero inoxidable	Cabinet in acciaio inossidabile Stainless steel cabinet Alojamiento en acero inoxidable	Cabinet in acciaio inossidabile Stainless steel cabinet Alojamiento en acero inoxidable
Potenza_Power_Potencia	46W	40W DC/40W AC	100W	270W
Dimensioni Dimensions Dimensiones	205x175x150 mm	205x175x150 mm	210x180x260 mm	202x379x285 mm
Volume flusso aria Airflow volume Volumen del flujo de aire	2 m ³ /min	2 m ³ /min	2 ÷ 4 m ³ /min	4,8 m ³ /min
Peso netto-lordo Net-gross weight Peso neto-bruto	2Kg/2,6Kg	2Kg/2,6Kg	2,9Kg/3,9Kg	6,2Kg/7,6Kg
Alimentazione: Power supply: Alimentación:	220/240V	12V DC / 2 20 - 240V AC	220/240V	210/230V
Trattamento aria Air treatment Tratamiento de aire	✓	✓	✓	—
Telecomando Remote control Control remoto	—	—	—	✓